



# GCL-P6/72

HIGH EFFICIENCY  
MULTICRYSTALLINE MODULE

**GCL-P6/72 310-330 Watt**

## 330<sup>W</sup>

MAXIMUM POWER OUTPUT

## 17.0 %

MAXIMUM MODULE EFFICIENCY

## 0~+5<sup>W</sup>

POWER OUTPUT GUARANTEE


### Trust GCL to Deliver Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard:  
ISO9001:2008, ISO 14001: 2004 and OHSAS: 18001 2007
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068-2- 68)
- Long term reliability tests
- 2\*100% EL inspection ensuring defect-free modules

### LINEAR PERFORMANCE WARRANTY

10 Years Product Warranty

25 Years Linear Power Warranty



Ideal choice for large scale ground installation



High conversion efficiency due to top quality wafer and advanced cell technology



Selected encapsulating material and stringent production process control ensure product highly PID resistant and snail trails free



Passed sand blowing test, salt mist test and ammonia test; flexible for harsh environments



Optimized system performance by module level current sorting



Special cell process ensures great performance in low irradiance environment



Additional yield and easy maintenance with high transparent self-cleaning glass

Additional insurance backed by Swiss RE



According to UL 1703



**Bringing Green Power to Life**

## HIGH EFFICIENCY MULTICRYSTALLINE MODULE

TYPE (STC)	GCL-P6/72 310	GCL-P6/72 315	GCL-P6/72 320	GCL-P6/72 325	GCL-P6/72 330
Maximum Power P <sub>max</sub> (W)	310	315	320	325	330
Maximum Power Voltage V <sub>m</sub> (V)	37	37.2	37.4	37.6	37.8
Maximum Power Current I <sub>m</sub> (A)	8.38	8.47	8.56	8.64	8.73
Open Circuit Voltage V <sub>oc</sub> (V)	45.4	45.6	45.8	46	46.2
Short Circuit Current I <sub>sc</sub> (A)	8.99	9.08	9.17	9.24	9.33
Module Efficiency (%)	16.0	16.2	16.5	16.7	17.0
Power Output Tolerance P <sub>m</sub> (W)	0~+5				

### ELECTRICAL DATA (NOCT)

Maximum Power P <sub>max</sub> (W)	224.45	227.14	231.2	234.61	237.71
Maximum Power Voltage V <sub>m</sub> (V)	33.6	33.8	34.1	34.3	34.5
Maximum Power Current I <sub>m</sub> (A)	6.68	6.72	6.78	6.84	6.89
Open Circuit Voltage V <sub>oc</sub> (V)	42.2	42.4	42.5	42.7	42.9
Short Circuit Current I <sub>sc</sub> (A)	7.19	7.30	7.38	7.46	7.58

## MECHANICAL DATA

Solar Cells	Poly 156.75×156.75mm (6 inches)
Cell Orientation	72 Cells (6×12)
Module Dimensions	1956×992×35mm (77 × 39.05 × 1.38 inches)
Weight	22.2 kg
Glass	High transparency solar glass 3.2mm (0.13 inches)
Backsheet	White
Frame	Silver, anodized aluminium alloy
J-Box	IP68 Rated
Cables	4.0mm² (0.006 inches²), 1200mm (47.2 inches)
Connector	Original MC4 or Compatible
Wind Load/ Snow Load	2400Pa/6000Pa*

## TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	$45 \pm 2^{\circ}\text{C}$
Temperature Coefficient of $P_{\text{MAX}}$	$-0.41\%/^{\circ}\text{C}$
Temperature Coefficient of $V_{\text{oc}}$	$-0.32\%/^{\circ}\text{C}$
Temperature Coefficient of $I_{\text{sc}}$	$+0.055\%/^{\circ}\text{C}$

## MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1000V DC(IEC)
Max Series Fuse Rating	15A

## WARRANTY

10 years Product Workmanship Warranty


25 years Linear Power Warranty

## PACKAGING CONFIGURATION


Modules per box: 30 pieces

Modules per 40'HD container: 720 pieces


## MODULE DIMENSION



Back View



### I-V CURVES OF MODULE(330W)



Excellent performance under weak light conditions: at an irradiation intensity of 200W/m<sup>2</sup> W/m(AM 1.5, 25 °C), 96.5% or higher of the STC efficiency (1000 W/m<sup>2</sup>) is achieved



<http://en.gclsi.com>

GCL-EN-P6/72-2017-V1.0

CAUTION: READ INSTALLATION MANUAL BEFORE USING THE PRODUCT

©2016 GCL System Integration Technology Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.